

*Sub
DT
E1*

~~changes [a change] in the measurement value with respect to a reference value;
calculating a time after a said vehicle will have sufficiently traveled after exiting the detection area so as to have substantially no influence on the period of the oscillator signal by~~

- ~~(i) determining the speed of a said vehicle and
(ii) calculating the time after vehicle exit based upon the vehicle speed and a predetermined distance from said detection area at which vehicle travel will not influence said period;~~

~~[vehicle exit from the detection area based upon a change in the measurement value during a time period subsequent to entry of the vehicle into the detection area;]~~

~~producing a sample measurement value at [based upon the signal after] the calculated time after vehicle exiting [of vehicle exit];~~

~~comparing a said reference value and the sample measurement value; and~~

~~adjusting the reference value, based upon the comparison.~~

E1 A7 cont.

~~2. (Amended) The method of claim 1 wherein the step of calculating a time of vehicle exit ^{after the vehicle exits from the detection area} further comprises: the step of~~

~~determining a time rate of change of inductance of the inductive sensor;~~

~~determining a magnitude of change of inductance;
and~~

*Sub
G2*

~~calculating vehicle speed based upon a predetermined entry distance and the ratio of the magnitude of change in inductance and the time rate of change [and the magnitude of change of inductance; and~~

~~calculating the time after vehicle exit based upon the vehicle speed].~~

3. (Amended) The method of claim 1 wherein ^{the step in} adjusting the reference value ^{further comprises the steps of} comprises:

setting the reference value equal to the sample measurement value if the difference between the reference value and the sample measurement value is greater than a predetermined threshold.

4. (Amended) The method of claim 1 ~~and~~ further comprising ^{the step of} setting the reference value equal to an average

of a plurality of sample measurement values, each measured after a vehicle has exited the detection area.

5. (Amended) A method of checking a reference value used in an inductive sensor vehicle detector, which comprises:

measuring frequency of an oscillator signal to produce a measurement value which is a function of inductance of the inductive sensor;

indicating presence of a vehicle if a difference between the measurement value and reference value exceeds a threshold;

measuring vehicle speed of a vehicle passing through a sensor area based upon a rate of frequency change and a magnitude of frequency change of the oscillator signal caused by the vehicle;

determining a time, based upon the vehicle speed, at which the vehicle will have sufficiently travelled after exiting [exited] the sensor area so as to have substantially no influence on the frequency of the oscillator

signal;
taking a sample measurement of the frequency of
the oscillator at the time that was
determined to be sufficient to allow the
vehicle to exit the sensor area; and
adjusting the reference value based upon the
sample measurement.

Sub
G4

A1 cont

6. (Amended) The method of claim 5 wherein
adjusting the reference value comprises:
determining a difference between a first sample
measurement value and the reference value;
adjusting the reference value to the first sample
measurement value if a difference between
them is greater than a predetermined level;
producing [taking] a predetermined number of
additional sample measurement values
[measurements], each after a vehicle has
been determined to have completed a pass
through the detection [sensor] area;
comparing the sample measurement values to
determine whether the ^{measurements} values are within a
predetermined range [measurements taken];
averaging the sample measurement values
[measurements] to produce an average sample
measurement value; and
adjusting the reference value to the average
sample measurement value if comparing shows
the sample measurement values are within
said predetermined range [measurements are
consistent with one another].

Sub
F1

7. (Amended) In a vehicle detector which
senses presence of a vehicle with an inductive sensor, a
method comprising:
measuring inductance of a dummy sensor which is
unaffected by the presence of a vehicle;

*Sub
F (Amended)*

E

~~comparing a currently measured inductance of the dummy sensor to a previously measured inductance of same dummy sensor; and determining, based upon the comparison of the currently and previously measured dummy sensor inductances, a change therebetween, and since the inductance thereof is unaffected by vehicles, recognizing a said change as indicative of an environmental factor unrelated to [whether a change in measured inductance of the inductive sensor is due to a factor which affects inductance of] the inductive sensor.~~

*Sub
G6
A7 CONT.
F*

*E
F
F*

~~8. (Amended) In a vehicle detector of a type in which an inductive sensor changes inductance in response to a vehicle, and in which an oscillator is connected to the inductive sensor to produce an oscillator signal having a frequency which is a function of inductance of the inductive sensor, a method of identifying a cause of changes in the oscillator signal frequency which are not caused by presence of a vehicle, the method comprising:~~

~~connecting the oscillator to a dummy sensor having ^{an} inductance which is not affected by vehicles;~~

~~measuring the frequency of an oscillator signal while the oscillator is connected to the dummy sensor;~~

~~comparing the frequency measured to a previously measured frequency of the dummy sensor; and determining, based upon the comparing, [whether] a change in the measured frequency, and since the inductance of the dummy sensor is not affected by vehicles, recognizing a said frequency change as ^{indicative} ~~an indication of an~~ ^{the} ~~environmental~~ change [frequency when the~~

oscillator is connected to the inductive sensor is due to a change in a factor] ~~not caused by a vehicle unrelated to the inductive sensor.~~

9. (Amended) A method for identifying changes in measured inductance of an inductive sensor used [mechanical difficulties associated] with a vehicle detector which [uses an] inductive sensor [which] changes inductance in response to presence of a said vehicle, but which identified changes are determined not to be caused by vehicles, and are, therefore, caused by mechanical difficulties requiring maintenance, the method comprising:

- measuring inductance of the inductive sensor over a plurality of measurement frame segments;
- calculating a time rate of change of inductance of the inductive sensor; and
- identifying existence of mechanical difficulties when the time rate of change of inductance calculated is in a predetermined range outside a threshold rate of change associated with vehicular movement.

10. (Amended) ~~In an inductive sensor system in which an inductive sensor is connected to an oscillator to produce an oscillator signal having a frequency which is a function of inductance of the inductive sensor, a method of identifying changes in frequency of the oscillator signal which are not produced in normal operation, and are, therefore, caused by mechanical difficulties which require maintenance activity to correct, the method comprising:~~

- ~~measuring a change in frequency of the oscillator signal over each of a plurality of measurement frame segments;~~
- ~~calculating ^athe rate of frequency change dF/dt of the ~~sensor drive~~ oscillator signal over the plurality of measurement frame segments;~~

Sub G8 (Amended)

~~determining whether the rate of frequency change dF/dt corresponds to a rate which does not occur during normal operations, and is, therefore, [is] indicative of mechanical difficulties; and~~
providing a signal indicating existence of mechanical difficulties.

11. (Amended) A method of adjusting a reference value of a vehicle detector which compares a measured value derived from an inductive sensor to a reference value, the method comprising:

A7 cont.

calculating a plurality of measurement periods [measurement period];
measuring a change in the measured value during each of said plurality of measurement periods [the measurement period];
comparing the change in each said [the] measured value to a threshold change; and
producing a new reference value based upon an average change in said measured values [the change in measured value] and the threshold change.

12. (Amended) The method of claim 11 wherein the new reference value is produced if the average change in the measured values [value] is less than the threshold change by adding the average change in the measured values [value] to the reference value.

F

13. (Amended) In a vehicle detector in which an inductive sensor is connected to an oscillator to produce an oscillator signal having a frequency which is a function of inductance of the inductive sensor, and in which presence of a vehicle is determined by comparing a measurement value which is a function of oscillator signal frequency to a reference value; a method of adjusting the reference value of a vehicle detector to reflect slow *compensate for drift*